



SECTION

NOTES:

1. THIS SECTION IS REQUIRED FOR CHANNELS WITH SANDY SOILS.
2. MAIN CHANNEL: CAPACITY TO BE FROM 2 YEAR TO THE 5 YEAR. MAXIMUM 100 YEAR FLOW VELOCITY IS 5 FPS. PROTECT SLOPES WITH RIPRAP. USE A MANNINGS N VALUE OF 0.03 FOR HYDRAULIC CALCULATIONS.
3. NORMAL DEPTH: FLOW DEPTH FOR 100 YEAR FLOW SHALL NOT EXCEED 5', NOT INCLUDING THE MAIN CHANNEL DEPTH.
4. FREEBOARD: FREEBOARD TO BE A MINIMUM OF 1'.
5. MAINTENANCE/ACCESS ROADS: MINIMUM WIDTH TO BE 10'. COUNTY MAY REQUIRE ALL OR PART OF THE ROAD TO BE SURFACED.
6. R/W WIDTH: MINIMUM WIDTH TO INCLUDE FREEBOARD AND MAINTENANCE/ACCESS ROAD.
7. OVERBANK: FLOW IN EXCESS OF MAIN CHANNEL TO BE CARRIED IN THIS AREA. AREA MAY BE USED FOR RECREATIONAL PURPOSES.

GRASS LINED CHANNEL, TYPE B
STANDARD DETAILS

CITY OF OWASSO, OKLAHOMA
PUBLIC WORKS DEPARTMENT
ENGINEERING DIVISION

DATE: 05/05

STANDARD NO. STRM-17